

Figure: 30 TAC §113.2174(g)

**Table 7. Requirements for Continuous Emission Monitoring Systems (CEMS)**

Pollutant	Span Values for CEMS	Performance Specifications (P.S.) in 40 CFR Part 60, Appendix B for your CEMS	If Needed to Meet Minimum Data Requirements, use the Following Alternate Methods in 40 CFR Part 60, Appendix A to Collect Data
1. Opacity	100 percent opacity	P.S. 1	Method 9
2. Nitrogen Oxides (Class I units only)	Control device outlet: 125 percent of the maximum expected hourly potential nitrogen oxides emissions of the municipal waste combustion unit	P.S. 2	Method 7E
3. Sulfur Dioxide	Inlet to control device: 125 percent of the maximum expected hourly potential sulfur dioxide emissions of the municipal waste combustion unit  Control device outlet: 50 percent of the maximum expected hourly potential sulfur dioxide emissions of the municipal waste combustion unit	P.S. 2	Method 6C
4. Carbon Monoxide	125 percent of the maximum expected hourly potential carbon	P.S. 4A	Method 10 with alternative interference trap

	monoxide emissions of the municipal waste combustion unit		
5. Oxygen or Carbon Dioxide	25 percent oxygen or 25 percent carbon dioxide	P.S. 3	Method 3A or 3B